

NEW OSHA REGULATION



Effective June 16, 2011

New OSHA Residential Construction Regulation in 2011

According to data from the department's Bureau of Labor Statistics, an average of 40 workers are killed each year as a result of falls from residential roofs. As a result, the Occupational Safety and Health Administration (OSHA) recently announced new fall protection requirements for Residential Construction.

The new directive requires all residential builders to comply with 29 Code of Federal Regulations 1926.501(b)(13). **Construction and roofing companies will have until June 16, 2011, to comply with the new directive.**

Under 29 CFR 1926.501(b)(13) workers engaged in residential construction over six (6) feet above the ground level are to be protected by conventional fall protection. For roofers, the 25 foot, ground-to-eave height threshold no longer applies, nor do slide guards as an acceptable form of fall protection, regardless of the roof pitch or height of the roof eave.

These new requirements replace the Interim Fall Protection Compliance Guidelines for Residential Construction, Standard 03-00-001 that have been in effect since 1995 and allowed residential builders to bypass fall protection requirements.

Construction and roofing companies will have up to six months (June 16, 2011) to comply with the new directive. OSHA has developed training and compliance assistance materials for small employers and will host a webinar for parties interested in learning more about complying with the standard.

For more information, go to: www.osha.gov/doc/residential_fall_protection.html

Innovative Miller Fall Protection Solutions



6.2011