



A460000

Fixed I-Beam Anchorage Connector

FEATURES

- Minimum Breaking Strength (MBS): 5,000 pounds
- Swivelling D-ring connection
- Adjustable for beam flange widths 4 to 14 inches and flange thickness ¼ to 1¼ inches.
- Meets ANSI Z359.18-2017
- Meets OSHA 1910.140 and 1926.502 requirements



SPECIFICATIONS

Model No.	Bar Material	Product Length	Minimum Breaking Strength (MBS)	Approx. Weight	Compliance Standards
A460000	Steel	27 in (0.69 m)	5,000 lbs (22.2 kN)	7.0 lbs (3.2 kg)	ANSI Z359.18-2017 OSHA 1910 & 1926

*See User Instructions for more information.

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet

WernerCo Corporate Headquarters: 555 Pierce Road, Suite 300, Itasca, IL 60143

TEL: 888-523-3370 FAX: (724) 588-0315 www.wernerco.com