


## Guide for 3M<sup>™</sup> ANSI Hard Hats, Headgear, and Faceshields



|   | 3M <sup>™</sup> H-Series Hard Hats/Headgear   |   |   |  |   |   |   |   |   |  |   |  |  |
|---|---|---|---|--|---|---|---|---|---|--|---|--|--|
|   | H24M  | H24T  | H18   | H18-S  | H8A   | H10   | H8A-S   | H700  | H800  | H700T                                      | X5000   |  |  |
|   |   | 3   |   |  |   |   |   |   |   |  |   |  |  |
| 3M ID   | 7000002292  | 7100113761  | 7000002291                                    | 7000052752   | 7000002290                                  | 7000052751  | 7000127237                                    | Various   | Various   | Various                                    | Various   |  |  |
| Product ID  | H24M  | H24T  | 82502-00000                                   | 82536-00000  | 82501-00000                                 | 82516-00000                                       | 82589-00000                                   | Various   | Various   | Various                                    | Various   |  |  |
| Key Benefits  | Hard Hat Faceshield<br>Holder, Allows use<br>of slots for hard hat<br>mounted ear muffs | Heat Resistant Hard Hat<br>Faceshield Holder,<br>Allows use of slots<br>for hard hat mounted<br>ear muffs | Hard Hat Slot<br>Mounted<br>Faceshield Holder | Hard Hat Slot<br>Mounted,<br>Heat Resistant<br>Faceshield Holder | Standard<br>Faceshield Holder               | Extended Crown<br>Coverage<br>Faceshield Holder   | Heat Resistant<br>Faceshield Holder           | Cap Style   | Full Brim   | Cap Style,<br>Elevated<br>Temperature      | Climbing Style  |  |  |
| Suspension Options Ratchet Pinlock  |   |   |   |  | R   | R   | R   | RP  | R   | R  | R   |  |  |
| Spark Def/Shell Material  | ABS   | Glass Nylon   | ABS   | Triax  | ABS   | ABS   | Triax   | HDPE  | HDPE  | Glass Nylon                                | ABS   |  |  |
| Radiant Heat Resistance<br>(Temperatures above standard test<br>temperatures of 120°F [49°C])                                       | 170°F (82°C)  | 375°F (190°C)<br>Radiant Heat   |   | 300°F (149°C)<br>Reflective                                      | 170°F (82°C)                                | 170°F (82°C)                                      | 300°F (149°C)<br>Reflective                   |   |   | 375°F (190°C)<br>Radiant Heat              |   |  |  |
| Non-Vented Models Available with ANSI Electrical Insulation   |   |   |   |  |   |   |   | CLASS E   | CLASS CLASS E   | CLASS                                      | CLASS CLASS E   |  |  |
| Color   | Blue/Silver   | Black/Silver  | Blue Spark<br>Deflector                       | Silver Spark<br>Deflector,<br>Gray Suspension                    | Blue Spark<br>Deflector,<br>Gray Suspension | Blue Crown/Spark<br>Deflector,<br>Gray Suspension | Silver Spark<br>Deflector,<br>Gray Suspension | •••••   | •••••   | ••○  | •••••   |  |  |
| Approximate Weight  | 4.8 oz (136 grams)  | 4.8 oz (136 grams)  | 5.5 oz (150 g)                                | 5.5 oz (150 g)   | 7.5 oz (212 g)                              | 9 oz (255 g)                                      | 7.5 oz (212 g)                                | 12 oz (343 g) Pinlock/<br>13 oz (366 g) Ratchet/<br>Plus 0.3 oz (8.5 g)<br>6 pt | 13 oz (380 g) Pinlock /<br>14 oz (403 g) Ratchet /<br>Plus 0.3 oz (8.5 g)<br>6 pt | 13 oz (375 g)<br>ratchet                   | Vented w/ magnetic<br>chinstrap: 17 oz (472 g)<br>Nonvented w/ plastic<br>chinstrap: 16 oz (453 g)<br>Suspension: 2.5 oz (70 g) |  |  |
| Suspension Size   |   |   |   |  | 6-3/4 in. to 8 in.<br>(17 cm to 20 cm)      | 6-3/4 in. to 8 in.<br>(17 cm to 20 cm)            | 6-3/4 in. to 8 in.<br>(17 cm to 20 cm)        | 6-5/8 in. to<br>7-3/4 in.<br>(17 cm to 20 cm)                                   | 6-5/8 in. to<br>7-3/4 in.<br>(17 cm to 20 cm)                                     | 6-5/8 in. to 7-3/4 in.<br>(17 cm to 20 cm) | 6-1/4 in. to 7-7/8 in.<br>(17 cm to 20 cm)  |  |  |
| ANSI Z87 Approved with Faceshield   | <b>•</b>  | <b>•</b>  |   | <b>O</b>   | <b>•</b>                                    |   | <b>O</b>                                      |   |   |  |   |  |  |
| ANSI Z89.1 Impact Rating  |   |   |   |  |   |   |   | TYPE  | TYPE  | TYPE                                       | TYPE  |  |  |
| ANSI Lower Temp Rating (LT)   |   |   |   |  |   |   |   | Tested to -22°F<br>(-30°C)  | Tested to -22°F<br>(-30°C)  |  | Tested to -22°F<br>(-30°C)  |  |  |
| ANSI Higher<br>Temp Rating (HT)   |   |   |   |  |   |   |   |   |   | Tested to 140°F<br>(60°C)                  |   |  |  |
| ANSI Reverse Donning  |   |   |   |  |   |   |   | <b>V</b>  | <b>•</b>  | <b>•</b>                                   |   |  |  |
| Optional Logo/Reflective hardhatcustomizer.3M.com   |   |   |   |  |   |   |   | LOGO REF  | LOGO REF  | LOGO REF                                   | LOGO REF  |  |  |
| 3M <sup>™</sup> UVicator <sup>™</sup><br>Sensor Models Available<br>Lets wearer know when to replace<br>hard hat due to UV exposure |   |   |   |  |   |   |   | V   | •   |  | <b>•</b>  |  |  |


| -3       | eyewe | ear, sold separately<br>/ith NRR 23 dB. |             | rainshield and<br>eyewear, sold | visor seal. Requires protective<br>I separately. With NRR 23 dB.   | an NRR of 25 dB or I  | H31A earmuffs with an NRR<br>of 24 dB.   | cutting drilling, and                       | d demolitio | on. fit                | ting, liquid hand<br>fueling, spraying | ling, line breaking<br>g, and painting. | <b>J</b> ,            |                           |                               |                        |                  | Sensoi<br>Lets wearer k<br>hard hat due | r Models Av<br>know when to replace<br>to UV exposure | railable                         |          |          |          |          |               |                 |               |   | $\overline{\mathbf{v}}$ |   | <b>Y</b>   |
|----------|-------|---|-------------|---------------------------------|--|---|--|---|-------------|------------------------|--|---|-----------------------|---------------------------|-------------------------------|------------------------|------------------|---|---|----------------------------------|----------|----------|----------|----------|---------------|-----------------|---------------|---|-------------------------|---|--|
|          |       | Product<br>Number                       | 3M ID       | Product<br>ID                   | Marketplace<br>Formal Name   | Potential<br>Application  | Key<br>Benefits  | Attachments Included Eacl                   | h/Case      | Faceshield<br>Material | Molded/<br>Flat                        | Thickness                               | Width                 | Height                    | ANSI High<br>Impact<br>(Z87+) | Outer<br>Coating       | Inner<br>Coating | Chemical<br>Resistant                   | ANSI<br>Light<br>Filters                              | Temp<br>Rating of<br>FS Material |          |          |          | Adapte   | rs for Hard H | ats/headgear an | nd faceshield | s/screens                                       |                         |   |  |
|          |       | W96                                     | 7100000260  | 82700-<br>00000                 | Clear Propionate Faceshield W96,<br>Face Protection 82700-00000,<br>Molded   | Chemical industry;<br>Spray painting                                      | Chemical Resistant   |   | 10          | Propionate             | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          |                               |                        |                  | <b>O</b>                                |   | 210°F/98°C                       |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |
|          |       | WP96                                    | 7000002339  | 82701-<br>00000                 | Clear Polycarbonate Faceshield<br>WP96, Face Protection<br>82701-00000, Molded   | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding            | Standard   |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          | <b>②</b>                      |                        |                  |   | U6  | 266°F/130°C                      | No       | Ad       | lap      | ter      | Ne            | ede             | d             | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |
|          |       | WP96X                                   | 7000127236  | 82582-<br>00000                 | Wide Clear Polycarbonate<br>Faceshield WP96X,<br>Face Protection 82582-00000,<br>Flat Stock                                      | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding            | Extended Side Coverage   |   | 25          | Polycarbonate          | Flat                                   | 0.04 in.<br>(0.1 cm)                    | 18.25 in.<br>(46 cm)  | 9 in.<br>(23 cm)          | V                             |                        |                  |   | U6  | 266°F/130°C                      |          |          | , "      |          | ı             |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |
|          |       | WE96X                                   | 7000127235  | 82581-<br>00000                 | Wide Clear PETG Faceshield<br>WE96X, Face Protection<br>82581-00000, Flat Stock  | Chemical industry;<br>Spray painting                                      | Chemical Resistant,<br>Extended Side Coverage  |   | 25          | PETG                   | Flat                                   | 0.04 in.<br>(0.1 cm)                    | 18.25 in.<br>(46 cm)  | 9 in.<br>23 cm)           |                               |                        |                  | <b>O</b>                                |   | 176°F/80°C                       |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WE96S                                   | 7000127234  | 82580-<br>00000                 | Short Clear PETG Faceshield<br>WE96S, Face Protection<br>82580-00000, Flat Stock   | Manufacturing   | Chemical Resistant,<br>Shorter Length,<br>Reduces Fogging                                |   | 50          | PETG                   | Flat                                   | 0.04 in.<br>(0.1 cm)                    | 14.5 in.<br>(37 cm)   | 7.5 in.<br>(19 cm)        |                               |                        |                  | <b>O</b>                                |   | 176°F/80°C                       |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WP96B                                   | 7000127232  | 82525-<br>00000                 | Polycarbonate Molded Medium<br>Green Faceshield Window WP96B,<br>Face Protection 82525-00000                                     | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Tinted for Moderately<br>Bright Environments   |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          | <b>②</b>                      |                        |                  |   | U6<br>S   | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WP96C                                   | 7000002340  | 82702-<br>00000                 | Dark Green Polycarbonate<br>Faceshield WP96C, Face Protection<br>82702-00000, Molded   | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Tinted for<br>Bright Environments  |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          | <b>▽</b>                      |                        |                  |   | U6<br>S   | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WP96AL                                  | 7000052705  | 82504-<br>00000                 | Aluminized Polycarbonate Molded<br>Clear Faceshield Window,<br>Face Protection 82504-00000                                       | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Blocks IR  |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          | <b>♥</b>                      | Aluminum               |                  |   | U6<br>W3.0  | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WP96BAL                                 | 7000052706  | 82518-<br>00000                 | Medium Green Aluminized<br>Polycarbonate Faceshield WP96BAL,<br>Face Protection 82518-00000                                      | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Blocks IR<br>Tinted for Moderately<br>Bright Environments                                |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          | <b>✓</b>                      | Aluminum               |                  |   | U6<br>W5  | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WP96CAL                                 | 7000127169  | 82509-<br>00000                 | Aluminized Polycarbonate Molded<br>Dark Green Faceshield Window,<br>Face Protection 82509-00000                                  | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Blocks IR<br>Tinted for Bright<br>Environments   |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          | <b>♥</b>                      | Aluminum               |                  |   | U6<br>W7  | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
| W-Series |       | WP96IR3                                 | 7000127240  | 82705-<br>10000                 | Polycarbonate Faceshield<br>Window W96IR3, Face Protection<br>82705-10000, Shade 3.0   | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Blocks up to<br>91% of IR Radiation  |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14 in.<br>(37 cm)     | 9 in.<br>(23 cm)          | V                             |                        |                  |   | U6<br>W3.0  | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WP96IR5                                 | 7000127241  | 82706-<br>10000                 | Polycarbonate Faceshield<br>Window W96IR5, Face Protection<br>82706-10000, Shade 5.0   | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Blocks up to<br>97.5% of IR Radiation  |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          | <b>♥</b>                      |                        |                  |   | U6<br>W5  | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WCP96                                   | 7000052753  | 82600-<br>00000                 | Total Performance Polycarbonate<br>Clear Faceshield Window WCP96,<br>Face Protection 82600-00000                                 | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Abrasion and<br>Fog Resistant Coatings   |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          | V                             | Anti Scratch           | Anti-fog         |   | U6  | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI witl<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WCP96B                                  | 7010384061  | 82601-<br>00000                 | Total Performance Polycarbonate<br>Medium Green Faceshield<br>Window WCP96B, Face Protection<br>82601-00000                      | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Tinted for Moderately<br>Bright Environments &<br>Abrasion and Fog<br>Resistant Coatings |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          | <b>♥</b>                      | Anti Scratch           | Anti-fog         |   | U6<br>S   | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WCP96G                                  | 7000127238  | 82602-<br>00000                 | Total Performance Gold-coated<br>Polycarbonate Clear Faceshield<br>Window WCP96G, Face Protection<br>82602-00000                 | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Higher IR Block  |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          | <b>✓</b>                      | Gold & Anti<br>Scratch | Anti-fog         |   | U6<br>W3.0  | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WCP96BG                                 | 7000144939  | 82603-<br>00000                 | Total Performance Gold-coated<br>Polycarbonate Medium Green<br>Faceshield Window WCP96BG, Face<br>Protection 82603-00000         | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Higher IR Block Tinted<br>for Moderately Bright<br>Environments                          |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          |                               | Gold & Anti<br>Scratch | Anti-fog         |   | U6<br>W5  | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          |       | WCP96CG                                 | 7000127239  | 82604-<br>00000                 | Total Performance Gold-coated<br>Polycarbonate Dark Green<br>Faceshield Window WCP96CG,<br>Face Protection 82604-00000           | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Higher IR<br>Block Tinted for<br>Bright Environments                                     |   | 10          | Polycarbonate          | Molded                                 | 0.08 in.<br>(0.2 cm)                    | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          | V                             | Gold & Anti<br>Scratch | Anti-fog         |   | U6<br>W7  | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attache<br>3M Earmuffs  |
|          | +     | WP98                                    | 7000002337  | 82543-<br>00000                 | Clear Polycarbonate Faceshield<br>WP98, Face Protection<br>82543-00000, Flat Stock   | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding, Foundries | Additional   |   | 10          | Polycarbonate          | Flat                                   | 0.04 in.                                | 14.5 in.<br>(37 cm)   | 7.25 in.                  | <b>⊘</b>                      |                        |                  |   | U6  | 266°F/130°C                      |          |          |          |          |               |                 |               | H24M  |                         | H24T  | U5B-ANSI with<br>P3EV/2-10P or                                   |
|          | -     | CP8                                     | 7000127233  | 82542-<br>00000                 | Replacement Clear Chin Protector<br>CP8, Face Protection 82542-00000   | N/A<br>Must be used<br>with WP98  | Chin Coverage  |   | 10          | Polycarbonate          | Molded                                 | (0.1 cm)                                |                       | (18 cm)                   |                               |                        |                  |   |   | 266°F/130°C                      |          |          |          |          |               |                 |               | H18   |                         | H18-S   | Helmet Attache<br>3M Earmuffs                                    |
|          |       | W96M                                    | 7000127168  | 82506-<br>00000                 | Steel Mesh Faceshield Screen<br>W96M, Face Protection<br>82506-00000, Molded   | Forestry;<br>Agriculture;<br>Brush cutting;<br>Trimming                   | Good Ventilation   |   | 10          | Steel Mesh             | Molded                                 |   | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          |                               |                        |                  |   |   |                                  |          |          |          |          |               |                 |               | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |
|          |       | W96MW                                   | 7000127231  | 82511-<br>00000                 | Steel Mesh Faceshield Screen<br>W96MW, Face Protection<br>82511-00000, with Clear Eyeshield                                      | Forestry;<br>Agriculture;<br>Brush cutting;<br>Trimming                   | Good Ventilation<br>and Clear Window<br>for Improved Visibility                          |   | 10          | Steel Mesh             | Molded                                 |   | 14.5 in.<br>(37 cm)   | 9 in.<br>(23 cm)          |                               |                        |                  |   |   |                                  | <u> </u> | <u> </u> | <b>+</b> | <b>↓</b> | <u> </u>      | <u> </u>        | <u> </u>      | H24M<br>H18                                     |                         | H24T<br>H18-S                                   | U5B-ANSI with<br>P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |
|          |       | V1A-10P                                 | 7000103808  | V1A-10P                         | PELTOR <sup>®</sup> Metal Mesh Faceshield<br>V1A-10P, Face Protection, Black   | Forestry;<br>Agriculture;<br>Brush cutting;<br>Trimming                   | Steel Mesh,<br>Great Ventilation   | V010 Linkage                                | 10          | Steel Mesh             | Molded                                 |   | 11.5 in.<br>(30 cm)   | 6.5 in.<br>(16.5<br>cm)   |                               |                        |                  |   |   |                                  |          |          |          |          |               |                 |               | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |                         | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |  |
|          |       | V1B-10P                                 | 7000103809  | V1B-10P                         | PELTOR™ Nylon Mesh Faceshield<br>V1B-10P, Face Protection, Black   | Forestry;<br>Agriculture;<br>Brush cutting;<br>Trimming                   | Nylon Mesh,<br>Great Ventilation   | V010 Linkage                                | 10          | Nylon Mesh             | Molded                                 |   | 11.5 in.<br>(30 cm)   | 6.5 in.<br>(16.5<br>cm)   |                               |                        |                  |   |   |                                  |          |          |          |          |               |                 |               | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |                         | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |  |
|          | *     | V2A-10P                                 | 7000103810  | V2A-10P                         | PELTOR™ Clear Acetate Faceshield<br>V2A-10P Face Protection  | Risk of exposure<br>to solid particles /<br>Chemical                      | Chemical Resistant,<br>Lightweight &<br>Improved Ventilation                             | V010 Linkage                                | 10          | Acetate                | Flat                                   | 0.04 in.<br>(0.1 cm)                    | 12.125 in.<br>(31 cm) | 8.25 in.<br>(21 cm)       |                               |                        |                  | <b>O</b>                                |   | 200°F/93°C                       |          |          |          |          |               |                 |               | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |                         | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |  |
| V1/V2/V3 |       | V2B-10P                                 | 7000103811  | V2B-10P                         | PELTOR™ Green Polycarbonate<br>Faceshield V2B-10P, Face Protection   | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding            | Tinted for Moderately<br>Bright Environments,<br>Lightweight &<br>Improved Ventilation   | V010 Linkage                                | 10          | Polycarbonate          | Flat                                   | 0.04 in.<br>(0.1 cm)                    | 12.125 in.<br>(31 cm) | 8.25 in.<br>(21 cm)       |                               |                        |                  |   | U6<br>S   |                                  |          |          |          |          |               |                 |               | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |                         | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |  |
|          |       | V2C-10P                                 | 7000103812  | V2C-10P                         | PELTOR™ Clear Polycarbonate<br>Faceshield V2C-10P, Face Protection   | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding            | Lightweight &<br>Improved Ventilation  | V010 Linkage                                | 10          | Polycarbonate          | Flat                                   | 0.04 in.<br>(0.1 cm)                    | 12.125 in.<br>(31 cm) | 8.25 in.<br>(21 cm)       | <b>⊘</b>                      |                        |                  |   | U6  | 266°F/130°C                      |          |          |          |          |               |                 |               | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |                         | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |  |
|          |       | V3C-10P                                 | NA          | V3C-10P                         | PELTOR <sup>™</sup> Clear Short Polycarbonate<br>Visor V3C-10P, Face Protection  | Manufacturing   | Short Visor. Lightweight<br>& Improved Ventilation                                       | V010 Linkage                                | 10          | Polycarbonate          | Flat                                   | 0.04 in.<br>(0.1 cm)                    | 12.125 in.<br>(31 cm) | 6.125 in.<br>(15.5<br>cm) |                               |                        |                  |   | U6  | 266°F/130°C                      |          |          |          |          |               |                 |               | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |                         | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |  |
|          | 400   | V3F-10P                                 | 7000103814  | V3F-10P                         | PELTOR <sup>™</sup> Clear Acetate Visor,<br>Face Protection V3F-10P  | Manufacturing   | Chemical Resistant,<br>Nose Cutout &<br>Improved Ventilation                             | V010 Linkage                                | 10          | Acetate                | Flat                                   | 0.04 in.<br>(0.1 cm)                    | 12.125 in.<br>(31 cm) | 5.5 in.<br>(14 cm)        |                               |                        |                  | •                                       |   | 200°F/93°C                       |          |          |          |          |               |                 |               | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |                         | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |  |
|          | Ű     | V4A-10P                                 | 70000103815 | V4A-10P                         | PELTOR-Steel Mesh MultiVisor <sup>™</sup><br>System V4A-10P Face Protection  | Forestry;<br>Agriculture;<br>Brush cutting;<br>Trimming                   | Steel Mesh,<br>Good Ventilation,<br>Adjustable Face to Shield<br>Distance                | V43 Visor Peak<br>Frame and V412<br>Linkage | 10          | Metal Mesh             | Flat                                   |   | 11.8 in.<br>(30 cm)   | 6.5 in.<br>(16.5 cm)      |                               |                        |                  |   |   |                                  |          |          |          |          |               |                 |               | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |                         | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |  |
| 47       | ~     | V4D-10P                                 | 7000103816  | V4D-10P                         | PELTOR <sup>™</sup> Clear Acetate MultiVisor <sup>™</sup><br>Faceshield System V4D-10P, Face<br>Protection with Anti-Fog Coating | Forestry;<br>Agriculture;<br>Brush cutting;<br>Trimming                   | Chemical Resistant,<br>Fog Resistant,<br>Adjustable Face to Shield<br>Distance           | V43 Visor Peak<br>Frame and V412<br>Linkage | 10          | Acetate                | Flat                                   | 0.04 in.<br>(0.1 cm)                    | 11.8 in.<br>(30 cm)   | 7 in.<br>(18 cm)          |                               |                        | Anti-fog         | <b>✓</b>                                |   | 200°F/93°C                       |          |          |          |          |               |                 |               | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |                         | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |  |
|          | ~     | V4F-10P                                 | 7000103817  | V4F-10P                         | PELTOR™ Clear Polycarbonate<br>MultiVisor™ System V4F-10P,<br>Face Protection  | Heavy industry;<br>Construction;<br>Metal working;<br>Grinding            | Lightweight,<br>Adjustable Face to Shield<br>Distance                                    | V43 Visor Peak<br>Frame and V412<br>Linkage | 10          | Polycarbonate          | Flat                                   | 0.04 in.<br>(0.1 cm)                    | 11.8 in.<br>(30 cm)   | 7 in.<br>(18 cm)          |                               |                        |                  |   | U6  | 266°F/130°C                      |          |          |          |          |               |                 |               | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |                         | P3EV/2-10P or<br>Helmet Attached<br>3M Earmuffs |  |

|                            | EarMuffs <sup>2</sup> — Compatible with H-700, H-700T AND X5000 |   |   |   |   |  |  |  |   |  |  |   |   |   |  |   |  |  |  |  |  |  |
|----------------------------|---|---|---|---|---|--|--|--|---|--|--|---|---|---|--|---|--|--|--|--|--|--|
|                            |   | 3M™ PELTOR™ X-Series Earmuffs                       |   |   |   |  |  |  |   |  |  |   |   |   |  |   | 3M <sup>™</sup> PELTOR <sup>™</sup> Optime <sup>™</sup> Earmuffs |  |  |  |  |  |
|                            | X1P3E   | X2P3E   | ХЗРЗЕ   | X4P3E   | X5P3E   | X1P5E  | X2P5E  | X3P5E  | X4P5E-OR  | X4P5E  | X5P5E  | X1P51E  | X4P51E  | H6P3E/V   | Н9РЗЕ  | Н7Р3Е   | H10P3E   | H31P3E   |  |  |  |  |
|                            |   |   |   |   |   |  |  |  |   |  |  |   |   |   |  |   |  |  |  |  |  |  |
| 3M ID                      | 7000104075  | 7000104076  | 7000104077  | 7000104078  | 7000104079  | 7100097525   | 7100097448   | 7100097405   | 7100097526  | 7100097429   | 7100097527   | 7100135816  | 7100135827  | 7000052743  | 7000002326   | 700009668   | 7000002327   | 7000141054   |  |  |  |  |
| Product ID                 | X1P3E   | X2P3E/37276(AAD)                                    | X3P3E/37277(AAD)                                    | X4P3E/37278(AAD)                                    | X5P3E37279(AAD)                                     | X1P5E  | X2P5E  | X3P5E  | X4P5E-OR  | X4P5E  | X5P5E  | X1P51E  | X4P51E  | H6P3E/V   | Н9Р3Е  | Н7Р3Е   | H10P3E   | H31P3E   |  |  |  |  |
| Marketplace<br>Formal Name | 3M™ PELTOR™<br>X1P3E Earmuffs,<br>Hard Hat Attached             | 3M™ PELTOR™<br>X2P3E Earmuffs,<br>Hard Hat Attached | 3M™ PELTOR™<br>X3P3E Earmuffs,<br>Hard Hat Attached | 3M™ PELTOR™<br>X4P3E Earmuffs,<br>Hard Hat Attached | 3M™ PELTOR™<br>X5P3E Earmuffs,<br>Hard Hat Attached | 3M™ PELTOR™<br>X1P5E Earmuffs,<br>Hard Hat Attached,<br>electrically insulated | 3M <sup>™</sup> PELTOR <sup>™</sup><br>X2P5E Earmuffs,<br>Hard Hat Attached,<br>electrically insulated | 3M™ PELTOR™<br>X3P5E Earmuffs,<br>Hard Hat Attached,<br>electrically insulated | 3M™ PELTOR™<br>X4P5E-OR Earmuffs,<br>Hard Hat Attached,<br>electrically insulated | 3M™ PELTOR™<br>X4P5E Earmuffs,<br>Hard Hat Attached,<br>electrically insulated | 3M <sup>™</sup> PELTOR <sup>™</sup><br>X5P5E Earmuffs,<br>Hard Hat Attached,<br>electrically insulated | 3M™ PELTOR™<br>X1P51E Full Brim<br>Hard Hat Attached,<br>electrically insulated | 3M™ PELTOR™<br>X4P51E Full Brim<br>Hard Hat Attached,<br>electrically insulated | 3M™ PELTOR™<br>Optime™ 95 Earmuffs<br>H6P3E/V,<br>Hard Hat Attached | 3M™ PELTOR™<br>Optime™ 98 Earmuffs H9P3E,<br>Hard Hat Attached | 3M™ PELTOR™ Optime™ 101<br>Earmuffs H7P3E, Hard Hat<br>Attached | 3M™ PELTOR™ Optime™ 105<br>Earmuffs H10P3E, Hard Hat<br>Attached | 3M™ PELTOR™<br>H31P3E Earmuffs,<br>Hard Hat Attached |  |  |  |  |
| Attachments<br>Included    | P3E w/ muffs  | P3E w/ muffs  | P3E w/ muffs  | P3E w/ muffs  | P3E w/ muffs  | P5 w/ muffs  | P5 w/ muffs  | P5 w/ muffs  | P5 w/ muffs   | P5 w/ muffs  | P5 w/ muffs  | P51 w/ muffs  | P51 w/ muffs  | P3E w/ muffs  | P3E w/ muffs   | P3E w/ muffs  | P3E w/ muffs   | P3E w/ muffs   |  |  |  |  |
| Each/Case                  | 10  | 10  | 10  | 10  | 10  | 10   | 10   | 10   | 10  | 10   | 10   | 10  | 10  | 10  | 10   | 10  | 10   | 10   |  |  |  |  |
| NRR <sup>3</sup>           | 21 dBA  | 24 dBA  | 25 dBA  | 25 dBA  | 31 dBA  | 21 dBA   | 24 dBA   | 25 dBA   | 25 dBA  | 25 dBA   | 31 dBA   | 20 dBA  | 26 dBA  | 21 dBA  | 23 dBA   | 24 dBA  | 27 dBA   | 23 dBA   |  |  |  |  |

|                        | H-Series Hard Hats/Headgear Spare Parts and Accessories                   |  |   |  |   |                                |  |                          |                                      |   |  |  | H-Ser  | ies Hard Hats/  | Headgear and 3   | BM <sup>™</sup> SecureFit <sup>™</sup>  | X5000 Spare P          | Parts and Acce          | ssories   | 3M™ SecureFit™ X5000 Spare Parts and Accessories⁴                                   |  |   |                   |   |   |                           |   |  |  |  |
|------------------------|---|--|---|--|---|--------------------------------|--|--------------------------|--------------------------------------|---|--|--|--|---|--|---|------------------------|-------------------------|---|---|--|---|-------------------|---|---|---------------------------|---|--|--|--|
|                        | H-700-RS4   | H-700-PS4  | H-700-BP  | H-700-S6   | NC2-GR  | FC1-AI                         | FC1-GR   | TCS1                     | H-SR-S                               | V43   | GR2B-10P   | X24  | P3EV/2-10P   | V901AF  | V902AF   | V903AF  | HL100                  | HL200                   | HL300IS   | X5-SV01   | X5-SV02  | X5-SV03   | U5B-ANSI          | X5-S4PTCS1                                    | X5-P4PTCS1  | X5-REFKIT                 | X5-SWBD01   | X5-6PTSUS  |  |  |
|                        |   | 0  |   |  |   |                                |  |                          | V                                    |   |  |  |  |   |  |   |                        |                         |   |   |  |   | <u></u>           | P <sub>1</sub>                                | A   | JT                        |   |  |  |  |
| 3M ID                  | 7000002421  | 7000002422   | 7000030093  | 7000053150   | 7010293216  | 7100082486                     | 7100082485                                     | 7100113757               | 7010341312                           | 7000103846  | 7000103819   | 7000029947   | 7000103847   | 7100101916  | 7100205236   | 7100205235  | 7010386281             | 7010316628              | 7010386282  | 7100176969  | 7100176970   | 7100176971  | 7100179142        | 7100175586                                    | 7100175588  | 7100175590                | 7100180680  | 7100180703   |  |  |
| Product ID             | H-700-RS4   | H-700-PS4  | H-700-BP  | H-700-S6   | NC2-GR  | FC1-AI                         | FC1-GR   | TCS1                     | H-SR-S                               | V43   | GR2B-10P   | X24  | P3EV/2-10P   | V901AF  | V902AF   | V903AF  | HL100                  | HL200                   | HL300IS   | X5-SV01   | X5-SV02  | X5-SV03   | U5B-ANSI          | X5-S4PTCS1                                    | X5-P4PTCS1  | X5-REFKIT                 | X5-SWBD01   | X5-6PTSUS  |  |  |
| Product<br>Description | Replacement<br>Ratchet<br>Suspension, Fits<br>H-700, H-800,<br>and H-700T | Replacement<br>Pinlock Suspension,<br>Fits H-700, H-800,<br>and H-700T | Replacement<br>Browpad, Fits<br>H-700, H-800,<br>and H-700T | Replacement<br>suspension strap to<br>be used with 4-point<br>pinlock or 4-point<br>ratchet suspension<br>for H-700, H-800<br>and H-700T | Attaches to H-700T<br>Hard Hat to help<br>provide posterior<br>neck protection<br>from molten<br>metal splash | Aluminum Front<br>Helmet Cover | Cotton +<br>Para-aramide<br>Front Helmet Cover | Terry Cloth<br>Sweatband | Reflective Strips<br>for H-700/H-800 | MultiVisor Brim,<br>Face Protection,<br>Replacement<br>for Visors | Hard Hat Front<br>Visor Seal<br>GR2B-10P,<br>Head Protection | Elastic Chin<br>Strap X24,<br>Head Protection<br>46551- 00000<br>for Helmet H700<br>and H800 | Adaptor for use<br>in Hard Hat slots<br>without PELTOR™<br>muffs | Integrated<br>Protective Eyewear<br>V901AF Clear<br>Anti-fog Lens,<br>ANSI Z87.1 2015 | Integrated<br>Protective Eyewear<br>V902AF Gray<br>Anti-fog Lens,<br>ANSI Z87.1 2015 | Integrated<br>Protective Eyewear<br>V903AF Amber<br>Anti-fog Lens,<br>ANSI Z87.1 2015 | 70 Lumen<br>Task Light | 150 Lumen<br>Task Light | 150 Lumen Task<br>Light, Intrinsically<br>Safe — Class I, II &<br>III and Div 1 & 2 | Short Visor,<br>Clear Anti-Fog<br>Anti-Scratch<br>Polycarbonate,<br>ANSI Z87.1 2015 | Short Visor,<br>Grey Anti-Fog<br>Anti-Scratch<br>Polycarbonate,<br>ANSI Z87.1 2015 | Short Visor,<br>Amber Anti-Fog<br>Anti-Scratch<br>Polycarbonate,<br>ANSI Z87.1 2015 | Faceshield Holder | Standard 4 Point<br>Chin Strap with<br>Buckle | Premium 4 Point<br>Chin Strap with<br>Magnetic Buckle | Reflective<br>Sticker Kit | Black/Grey<br>Replacement<br>Sweat Band<br>for SecureFit<br>Safety Helmet | Replacement 6 Point Suspension for SecureFit Safety Helmet |  |  |
| Each/Case              | 20  | 20   | 20  | 20   | 10  | 1                              | 1  | 10                       | 20                                   | 1   | 10   | 10   | 5  | 20  | 20   | 20  | 10                     | 10                      | 10  | 10  | 10   | 10  | 10                | 1   | 1   | 10                        | 10  | 10   |  |  |

<sup>1.</sup> All faceshields meet ANSI Z87.1 and must be worn with protective eyewear. 2. All 3M earmuffs listed are tested to ANSI S3.19-1974.

<sup>3.</sup> U.S. EPA specifies the NRR as the measure of hearing protector noise reduction. However, 3M makes no warranties as to the suitability of the NRR for this purpose. 3M strongly recommends personal fit testing of hearing protectors. Research suggests that users may receive less noise reduction than indicated by the attenuation label value(s) on the packaging due to variation in fit, fitting skill, and motivation of the user. Refer to applicable regulations or guidance on how to adjust attenuation label values. It is recommended that the NRR be reduced by 50% to better estimate typical protection. 4. Not all accessories are rated for elevated temperatures. For additional product ratings, see product label.







For More Information Technical Assistance 1-800-243-4630 Hours of Operation: 8:00 a.m. – 4:30 p.m. CST Customer Care Center 1-800-328-1667 Hours of Operation: 7:00 a.m. – 5:00 p.m. CST 3M.com/workersafety

70-0717-6090-7