



## Cortez® ANSI • CE •



Durable co-injected temples  
// Ribbed cushioned nosepiece

### Black Temples | 4 Variations

	SB 3610S ••	Clear
	SB 3610ST ••	Clear H2X AF
	SB 3620S ••	Gray
	SB 3680S ••	I/O Mirror

### Orange Temples | 1 Variation

	S03610S •	Clear
--	-----------	-------





SG 36



S036

### Gray Temples | 2 Variations

	SG 3610S •	Clear
	SG 3620S •	Gray

### Navy Temples | 1 Variation

	SN 3610S •	Clear
---	------------	-------



SN 36

### General Specifications

Weight: 23 gm  
 PD: 68 mm  
 Bridge: 12 mm  
 Lens base: 9.5 curve  
 Lens size diagonal: 70 mm  
 Lens size vertical: 43 mm  
 Lens thickness: 2.20 mm  
 Overall length [lens - tip]: 157 mm  
 Overall width [hinge - hinge]: 137 mm  
 Closest point between temple tips: 73 mm  
 Closest point between lens: 15.5 mm

### Materials

Lens: polycarbonate  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Nosepiece: polycarbonate & polyvinyl chloride (PVC)

### Part No.

SB 3610S  
 SB 3610ST  
 SB 3620S  
 SB 3680S  
 SG 3610S  
 SG 3620S  
 S03610S  
 SN 3610S

### Lens Marking

P Z87 + U6  
 P Z87 + U6  
 P Z87 + U6 L2.5  
 P Z87 + U6 L1.7  
 P Z87 + U6  
 P Z87 + U6 L2.5  
 P Z87 + U6  
 P Z87 + U6

### Temple Marking

P Z87 +  
 P Z87 +  
 P Z87 +  
 P Z87 +  
 P Z87 +  
 P Z87 +  
 P Z87 +  
 P Z87 +

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact